DUAL STAGE GAS VOLUME TANK HBD-2459-G & HBD-2459-H



Ounce Gauge

PSI

Gauge

Ounce Regulator

> Fuel Gas Safety Shutdown valve

1" NPT GAS

SUPPLY

INLET

12" x 18" Base

Float

HIGH PRESSURE CHAMBER Valve Assembly

HBD-2459-G

Arrow gas volume tanks are designed to give your engine long life and full power by furnishing clean and more even flow of gas under all conditions. These two-stage tanks can be placed on any flat surface. HBD-2459-H now also available in ASME code upon request.

Arrow Part #

v Part #	HBD-2459-G	HBD-2459-H
Size	6″	10″
MAWP	15 psig	15 psig
at Temp	100°F	100°F
Volume	1089 in ³	3200 in ³



HBD Nameplate allows space for a custom distributor logo to be added.



Includes Arrow S-102-4 Regulator. Maximum psi to the tank not to exceed 15 psi. Total height from top of ounce regulator to base = 48" (4 ft.)

Condensate Drain Valves LOW

PRESSURE

CHAMBER

1" NPT

OUTLET

HBD-2459-G-H-ML-F-FEB16

Arrow Engine Company 2301 East Independence, Tulsa, Oklahoma 74110

www.ArrowEngine.com

toll free (800) 331-3662 local (918) 583-5711 fax (918) 699-2202